



INSIDE DIA. IN.	JOINT DIA. IN.	JOINT DEPTH IN.	GASKET DIA. IN.	WALL 'T' IN.	WEIGHT LBS./ FT.	LAID LENGTH FT.	ASTM C-76 (IN. SQ./FT.)					
							CLASS 3		CLASS 4		CLASS 5	
							INSIDE	OUTSIDE	INSIDE	OUTSIDE	INSIDE	OUTSIDE
36	39	3-3/8	21/32	4-3/4	646	20.03	0.08	0.07	0.14	0.08	0.27	0.16
42	45	3-3/4	21/32	4-1/2	698	20.03	0.21	0.13	0.35	0.21	0.60	0.36
48	51-1/4	3-7/8	21/32	5	885	20.03	0.24	0.14	0.42	0.25	0.73	0.44
54	57-3/4	4-1/8	25/32	5-1/2	1092	20.03	0.29	0.17	0.50	0.30	0.86	0.52
60	63-7/8	4-1/4	25/32	6-3/4	1504	20.03	0.25	0.15	0.41	0.25	0.70	0.42
66	70-1/8	4-3/8	25/32	7-1/4	1773	20.03	0.31	0.19	0.51	0.31	0.84	0.50
72	76-3/8	4-1/2	25/32	7-3/4	2063	20.03	0.36	0.22	0.61	0.37	0.99	0.59
78	82-1/2	4-5/8	25/32	8-1/4	2375	20.04	0.42	0.25	0.71	0.43	1.25	0.75
84	88-3/4	4-7/8	25/32	8-3/4	2709	20.04	0.50	0.30	0.85	0.51	1.37	0.82

NOTES:

- 1) STANDARD SPECIFICATIONS AWWA C-302 & ASTM C-361.
- 2) SPECIAL DESIGNS FURNISHED UPON REQUEST.

VIANINI PIPE, INC.

TITLE: 36" THRU 84" V-1
 REINFORCED CONCRETE PIPE
 WITH RUBBER & STEEL JOINTS (V-1)